

Nelson & Nelson Mfg.

2200 Fowler Ave, Suite D Jonesboro AR 72401 870-268-6393 : Cell 219-1019

Installation Instructions 8-23-19

Model RYK-GRL

Front Grille Guard

Steps needed to install your Ryker Grille Guard

1.- Installing the new Grille Guard is simple. Only four bolts! First remove the LOWER two factory 6mm bolts that secure the front Ryker Grille. These are shown in the photo below as black bolts if you Ryker has them. Remove them to allow the Grille Guard to be installed. Next place the Grille Guard in front of the Grille and secure in place by using the longer 6mm Stainless Steel bolts supplied. Do not tighten at this point. If you have a Ryker Rally Edition, some units may or may not have the factory 6mm Black Bolts and U-Clips installed. If not see below on how to install the supplied bolts and clips



Bottom View of Your Ryker.



2.- Take the Supplied 3/8" bolts and place the supplied spacer as shown above. The spacer is located between the skid plate of the Grille Guard and the angled slotted gusset brace each side of the frame. Install the washer on top of the frame then the locknut.

Align the Grille Guard assuring the spacing between the Grille Guard and the front Grille is parallel.

Then tighten down the front 6mm bolts and then the rear 3/8" main bolts.

3.- . If you have a Ryker Rally Edition, some units may or may not have the U-Clip Nut shown below in that the 6mm bolt will screw too. If your Rally does not have this U-Clip Nut install the supplied U-Clip Nut and bolt. Its best to add medium strength Loctite to these two bolts before installing. The Clip will clip over the metal tab on the frame as shown below.

Once all is tightened the Grille Guard is installed!





Completed Install with Optional LED Day time Running Light / Driving Light!

We thank you for purchasing our Ryker Grille Guard. We know today the needs for Quality Accessories, and we have solved that demand with a stylish system that compliments the design of your NEW Ryker®!