

## Nelson & Nelson Mfg. 5210 Stadium Blvd, Suite C Jonesboro AR 72404 870-268-6393 : Cell 219-1019

Installation Instructions 4-28-24

## **Model CAN-BT**

## **CANYON Patented Belt Tensioner**

## Steps needed to install your SE Performance Belt Tensioner for 2025+ Canyon Models



1.- First remove the lower trim panel as shown below. First with a T-30 driver remove the lower right-side bolt as shown below. Then pull that lower right side outward and remove that lower trim panel. Next with the same T-30 driver remove the two bolts shown that hold the upper panel in place.



2.-Next remove the upper panel as shown below. Then remove the push pin as shown.



3.- With a T-30 driver remove the upper screw as shown. Then remove the upper panel. Pull the upper right panel outward to unclip and then slide rearwards to remove.



3.-Once the panel is removed, locate the factory belt tensioner as shown below.

With a 10mm socket remove the two factory bolts. Then take your new belt tensioner and place it in the same position as the factory was.



4.- Once in place take the two factory bolts and secure the new tensioner in place but do NOT tighten down. Tight down the bolts just enough to allow adjustment of the tensioner. The Belt Tensioner should run parallel to the belt with the roller aligned centered on the belt running perpendicular to the belt. Once aligned then tight down the two 10mmk bolts. Make sure the tensioner stays aligned while tightening down. Once tight you can lift the tensioner arm to make sure it's properly working and aligned. Then reinstall both side panels in reverse of how they were removed and reinstall the driver's seat.



Your new SE Performance Belt Tensioner is now installed and will provide miles and miles of satisfaction on your new Canyon!