



Nelson & Nelson Mfg.
5210 Stadium Blvd. Suite C
Jonesboro AR 72404
870-268-6393 : Cell 219-1019

Installation Instructions 11-17-25

Model RYK-SMNT

For all Ryker Models using the OEM Max Mount

Steps needed to install your Ryker Universal (on most models) Trunk Mount.

DO NOT USE IMPACT DRILL ON BOLTS OR NUTS.



Complete Kit shown above.

- 1.- Take the (4) 6mm flanged bolts and secure the Mount to the bottom of the Max Mount. The four slots shown below allows the Mount to be adjusted as needed.



When installing the new bolts use Loctite Blue Thread Locker on all bolts

If you plan on using the trunk for carrying heavier objects, remove the passenger seat and use the two supplied button head bolts in lieu of the 6mm bolts for the rear two bolts. To make them fit use a small right-angled drill on the underside of the max mount, drill out the two rear 6mm threaded stubs on the underside of the max mount shown below using a 1/4" drill bit now creating a 1/4" hole.

Do this on both rear side max mount holes. Then use the supplied bolts washers and locknuts to secure the trunk mount. This will help to support the additional weight. Finish by using two of the 6mm bolts on the front two max mount holes, then reinstall the rear passenger seat.



Be sure to remove all drill shavings once completed.

2.- Once the Mount is installed you can take the luggage system of your choice and follow the manufacturer's instructions and install that mount to the luggage mount using the hardware supplied by the manufacturer. If you need to drill additional holes because your base mount does not match these existing holes you may do so for proper mounting to your specific model. Some Givi models require additional holes to mount the base plate.

We thank you for purchasing one of our Ryker Accessory Kits. Today we know the need for accessories that provide a higher level of comfort while riding and we have solved that demand with a stylish system that compliments the design of your Ryker!

Spyderextras.com